

Technical Data Sheet

River Mat - RM-100

Fibre	excelsior
Fibre Content (%)	100%
Width (m)	1,22
Length (m)	3,00
Area (sqm)	3,66
Weight per roll (kg)	~ 5
Weight / Total (gr./m²)	1500
Weight / Fibre (gr./m²)	500
Functional Longevity (months)	6 - 12
Top netting	Natural - jute
Top netting weight (gr./m²)	500
Top netting size	Approx. 18 x 12
Top netting tensile strength DIN53857	750 (MD) / 450 (TD) daN/m
Bottom & side netting	Natural - jute
Bottom & side netting weight (gr./m²)	225gr. x 2 layers
Bottom & side netting size	2 x 2mm

Application:

GREENFIX RiverMats are useable in natural and artificial channels. Each roll consists of 2 layers of burlap, all-for-sides closed.

The specifications presented herein are to the best of our knowledge true and accurate. GREENFIX cannot guarantee or warranty our products, unless agreed to in writing for specific conditions, for performance since the manner of handling; use and installation are beyond our control.

We cannot warrant our products to perform under unlimited circumstances due variables such as soil conditions, manner of installation and particularly severe weather conditions. Satisfactory results may not meet your expectations. No one can guarantee that required moisture will occur to permit growth after seed germination. We will not be liable for damages or losses, direct or indirect, of our GREENFIX Range of Products due to the above reasons.

Latest-Update: July 30, 2014 Name: Kai Tietjen File Name: RM-100

Copyright of these GREENFIX Document is reserved by SOILTEC GmbH. Copying or transmission of these document in whole or in part or any information contained therein is strictly prohibited without the prior authorization of SOILTEC GmbH, Germany.

